RFID TAG

RFID HANGTAG



FREQUENCY

Global 860 to 960 MHz

STANDARD SIZE

75 × 50 mm, 87 × 41 mm

SURFACE MATERIAL

200gsm Art Paper / Coated Paper

The RFID Hangtag combines brand presentation with UHF passive RFID (EPC Class 1 Gen 2 / ISO 18000-6C) inventory visibility for retail and apparel. Standard apparel sizes are 75 × 50 mm and 87 × 41 mm, on 200gsm or 250gsm art/coated paper or 200gsm white card, with custom materials on request. Tags operate across global 860 to 960 MHz and support color or monochrome printing, customized sizes, and variable data printing and encoding.

APPLICATIONS

- Retail & Apparel
- Product Authentication
- Brand Protection
- Inventory Management

FEATURES

01 200gsm / 250gsm art or coated paper, 200gsm white card or custom materials

02 75 × 50 mm and 87 × 41 mm standard apparel sizes

03 Color or monochrome printing

04 Variable data printing and encoding

05 Shipped in rolls or single pieces

TECHNICAL SPECIFICATIONS

Surface Material	200gsm Art Paper / Coated Paper, 250gsm Art Paper / Coated Paper, 200gsm White Card Paper, Custom materials available upon request.
Type	UHF Passive RFID (EPC Class 1 Gen 2 / ISO 18000-6C)
Packing	Shipped in rolls, Shipped in single pieces
Other Customized Services	Color/monochrome printing., Customized size design., Variable data printing and encoding.